



Procurement Unit

REQUEST FOR QUOTATION (RFQ) No. 516-2022

The Tarlac State University (TSU), through its Bids and Awards Committee (BAC) and Procurement Unit, will undertake an **Alternative Method of Procurement through Negotiated Procurement** for the items stated below, in accordance with **Section 53.9 Small Value Procurement** of the Revised Implementing Rules and Regulations of Republic Act. No. 9184.

The TSU hereinafter referred to as "the Buyer", now requests submission of a price quotation for the subject below:

Purchase Request No.	DESCRIPTION/PARTICULARS	APPROVED BUDGET FOR THE CONTRACT (ABC) inclusive of VAT
2022-09-281 (PCSU)	VARIOUS SAFETY EQUIPMENT	988,000.00

Purpose: for the operationalization of face-to-face classes.

Philgeps Posting: Active Date: 9-30-22 Closing Date: 10-6-22 Category: Safety & Occupational Protection Reference No.: 9064174

Interested suppliers are required to submit the following documents:

- Valid and Current Mayor's / Business Permit
- Latest Income / Business Tax Return
- Proof of PhilGeps Registration
- Omnibus Sworn Statement
- Brochure, if applicable

TSU Condition of Sale:

- Delivery Schedule: 30 calendar days from receipt of approved PO/NTP
- Bid Validity: 120 calendar days from submission of bids
- Delivery Site: Supply and Property Management Unit, Tarlac State University (045) 606-8159 / (045) 982-2605
- Warranty shall be for a period minimum of three (3) months of expendable supplies, or a supplies/equipment after acceptance by the procuring entity of the delivered

Award of contract shall be made to the bidder with the lowest quotation for the subject goods which comply with the minimum technical specifications and other terms and conditions stated herein.

Any alteration, erasures, or overwriting shall be valid only if they are signed or initialed by the bidder or his/her duly authorized representative.

Submission of duly signed Price Quotation Form (Attachment 1-3) and eligibility documents is not later than 10-6-22 at the Procurement Unit, Admin Building Tarlac State University, Tarlac City.

Open submission may be done manually or through email at tsucanvassing@gmail.com / julietelaineacuna@yahoo.com / javy_carlos@yahoo.com

The penalty for late deliveries is one tenth (1/10) of one (1) percent of the cost of the underperformed portion for every day of delay. Once the cumulative amount of liquidated damages reaches ten (10%) percent of the contract price, the procuring entity shall rescind the contract without prejudice to other courses of action and remedies open to it.

The TSU reserves the right to reject any and all bids, declare a failure of bidding, or not award the contract in accordance with Section 41 of R.A 9184 and its IRR, without thereby incurring any liability to the affected bidder or bidders.


ELENA MAY T. TEOFILO
 Head, Procurement Unit

PRICE QUOTATION

Date: 9/27/2022
 RFQ No. 516-2022
 PR No. 2022-09-281 (PCSU)

The Bids and Awards Committee
 c/o Procurement Unit
 TSU, Tarlac City
 (045) 982 -4630 / (045) 606 -8157

Sir / Madam:

After having carefully read and accepted the terms and conditions in the Request for Quotation, hereunder is our price quotation for the item/s identified below:

ITEM NO.	UNIT	ITEM & DESCRIPTION	QUANTITY	UNIT PRICE	TOTAL PRICE
1	unit	Portable Thermal Fogger Machine Disinfection Fogging Misting , Fuel Tank Capacity: 1.6L, Max Spray Volume: 90L/H, Medicine Box Capacity: 12L, The distance of water mist can reach 9-14 meters, the distance of smoke can reach 20-50 meters, and the spray range is wide. Fuel: No. 92 gasoline or above pure fuel. Ignition power supply: 12V rechargeable battery. Start mode: manual pull rope, electric button. Main functions: spraying pesticides, sterilization, humidification, dust prevention and other functions. Gross weight: 12.5kg. Packing size: 116*32*41cm.	12		
2	unit	Light Lux Meter , High accuracy of $\pm(5\%$ reading + 0.5%FS), MIN/MAX feature stores maximum and minimum readings, Data Hold freezes reading in the display, Large LCD display with analog bargraph, Backlight for readings in low light levels	1		
3	set	Heavy Duty Hot Wire Thermo-Anemometer Telescoping Probe is ideal for measuring in HVAC ducts and other small vents; extends up to 7ft (2.1m) maximum length with cable <ul style="list-style-type: none"> • Built-in RS-232 PC serial interface for connection to PC • Extra large 1.4" (36mm) dual LCD display • MAX/MIN, Data Hold • Complete with telescoping probe with cab 	1		

Warranty : _____

The above-quoted price is inclusive of all costs and applicable taxes

Very truly yours,

AUTHORIZED REPRESENTATIVE:

Signature : _____
 Printed Name : _____
 Date : _____
 Company Name Registered : _____
 E-mail Address : _____
 Contact no. : _____

BANK DETAILS:

Bank Name : _____
 Bank Address : _____
 Bank Account Name : _____
 Bank Account Number : _____

PRICE QUOTATION

Date: 9/27/2022
 RFQ No. 516-2022
 PR No. 2022-09-281 (PCSU)

The Bids and Awards Committee
 c/o Procurement Unit
 TSU, Tarlac City
 (045) 982 -4630 / (045) 606 -8157

Sir / Madam:

After having carefully read and accepted the terms and conditions in the Request for Quotation, hereunder is our price quotation for the item/s identified below:

ITEM NO.	UNIT	ITEM & DESCRIPTION	QUANTITY	UNIT PRICE	TOTAL PRICE
4	unit	Sound Level Meter/Datalogger High accuracy ± 1.4 dB meets ANSI and IEC 61672-1 Type 2 standards, 30 to 130dB measurement range, Auto or Manual ranging, AC analog output for connection to an analyzer or recorder, Large backlit LCD display, Stores 99 readings manually and 20M readings via 2G SD card, Datalogger date/time stamps and stores readings on an SD card in Excel® format for easy transfer to a PC, User programmable sampling rate: 1 to 3600 seconds Min/Max, Data Hold, Auto Power Off, Built-in PC interface, Complete with 6 AA batteries, SD Card, wind screen	1		
5	set	Two-way Radio , Includes: Battery Pack, rubber duck antenna, charger, belt clip and owner's manual General Specifications: Frequency Range VHF136-174MHz UHF400-470MHz. , Frequency stability ± 2.5 ppm. Rated voltage DC7. , 2V Rechargeable lithium battery. , Memory channels 2x128 channels. Antenna configuration Add a sense antenna. Antenna impedance 50. Work method: The same frequency simplex. or different frequency simplex. Size HxLxW 110x58x32mm without antenna.	20		

Warranty : _____

The above-quoted price is inclusive of all costs and applicable taxes

Very truly yours,

AUTHORIZED REPRESENTATIVE:

Signature : _____
 Printed Name : _____
 Date : _____
 Company Name Registered : _____
 E-mail Address : _____
 Contact no. : _____

BANK DETAILS:

Bank Name : _____
 Bank Address : _____
 Bank Account Name : _____
 Bank Account Number : _____

PRICE QUOTATION

Date: 9/27/2022
 RFQ No. 516-2022
 PR No. 2022-09-281 (PCSU)

The Bids and Awards Committee
 c/o Procurement Unit
 TSU, Tarlac City
 (045) 982 -4630 / (045) 606 -8157

Sir / Madam:

After having carefully read and accepted the terms and conditions in the Request for Quotation, hereunder is our price quotation for the item/s identified below:

ITEM NO.	UNIT	ITEM & DESCRIPTION	QUANTITY	UNIT PRICE	TOTAL PRICE
		Transmit section: Output power high low 5W. Modulation broadband narrowband 16KF 3E 11KF 3E. Maximum frequency deviation broadband narrowband 5KHz 2. 5KHz. Adjacent channel power-65dB 60dB. Spurious power 7. 5uV. Pre-emphasis characteristic6dB. Emission current 1. 6A 5W. CTCSS CTCSS frequency deviation broadband narrowband 0. 5KHz±0. 1KHz 0. 4KHz±0. 1KHz. Modulation sensitivity8-12mV. Modulation distortion-5-Receive section. Reference sensitivity-122dBm 12dB SINAD. Audio power1W. Audio distortion-10-Block 85dB. Intermodulation. broad band narrow band. 60dB 55dB. Adjacent Channel Selectivity. Wide narrow. 65dB 60dB. Clutter suppression 65dB. What s in the Box. TK-F8 x1. Antennax1. Li-ion Battery Pack x1. Adapter x1. Chargerx1. Belt Clipx1. User s Manualx1			
6	set	Dual Retractable Stanchion Post Dual Belt, Stainless Material, Silver or Black post color, Belt: Up (Red) - Down (Red) or Up (Black) - Down (Black), Post Height: 36 Inches, Belt Length: Standard Size of 2 meters, Base Weight: 8 kgs.	50		
7	unit	Fogging Solution: Bac-To-Zero Specifications: Revolutionary mist system, Complete interior coverage, Kills bacteria fast, Size Available: 1000mL	100		

Warranty : _____

The above-quoted price is inclusive of all costs and applicable taxes

Very truly yours,

AUTHORIZED REPRESENTATIVE:

Signature : _____
 Printed Name : _____
 Date : _____
 Company Name Registered : _____
 E-mail Address : _____
 Contact no. : _____

BANK DETAILS:

Bank Name : _____
 Bank Address : _____
 Bank Account Name : _____
 Bank Account Number : _____



Bid Notice Abstract

Request for Quotation (RFQ)

Reference Number 9064174
Procuring Entity TARLAC STATE UNIVERSITY
Title Various Safety Equipment
Area of Delivery Tarlac

Solicitation Number: 516-2022	Status	Pending
Trade Agreement: Implementing Rules and Regulations	Associated Components	3
Procurement Mode: Negotiated Procurement - Small Value Procurement (Sec. 53.9)	Bid Supplements	0
Classification: Goods	Document Request List	0
Category: Safety and Occupational Products	Date Published	30/09/2022
Approved Budget for the Contract: PHP 988,000.00	Last Updated / Time	29/09/2022 07:42 AM
Delivery Period: 30 Day/s	Closing Date / Time	06/10/2022 13:00 PM
Client Agency:		
Contact Person: Juliet Elaine Acuna Canvasser Romulo Blvd. Tarlac City Tarlac Philippines 2300 63-045-6068157 julietelaineacuna@yahoo.com		

Description

for PCSU use

Line Items

Item No.	Product Name	Description	Quantity	Unit	Amount (PHP)
1	Portable Thermal Fogger Machine Disinfection Foggi	Fuel Tank Capacity: 1.6L, Max Spray Volume: 90L/H, Medicine Box Capacity: 12L, The distance of water mist can reach 9-14 meters, the distance of smoke can reach 20-50 meters, and the spray range is wide. Fuel: No. 92 gasoline or above pure fuel. Igni	12	Unit	180,000.00
2	Light Lux Meter	High accuracy of ±(5% reading + 0.5%FS), MIN/MAX feature stores maximum and minimum readings, Data Hold freezes reading in the display, Large LCD display with analog bargraph, Backlight for readings in low light levels	1	Unit	50,000.00
3	Heavy Duty Hot Wire Thermo-Anemometer Telescoping	is ideal for measuring in HVAC ducts and other small vents; extends up to 7ft (2.1m) maximum length with cable • Built-in RS-232 PC serial interface for connection to PC • Extra large 1.4" (36mm) dual LCD display • MAX/MIN, Data Hold • Complete with	1	Set	50,000.00
4	Sound Level Meter/Datalogger	High accuracy ±1.4dB meets ANSI and IEC 61672-1 Type 2 standards, 30 to 130dB measurement range, Auto or Manual ranging, AC analog output for connection to an analyzer or recorder, Large backlit LCD display, Stores 99 readings manually and 20M readin	1	Unit	50,000.00
5	Two-way Radio	ncludes: Battery Pack, rubber duck	20	Set	108,000.00

		antenna, charger, belt clip and owner's manual General Specifications: Frequency RangeVHF136-174MHz UHF400-470MHz. , Frequency stability±2. 5ppm. Rated voltageDC7. , 2V Rechargeable lithium battery. , Memory channe			
6	Dual Retractable Stanchion Post Dual Belt	Stainless Material, Silver or Black post color, Belt: Up (Red) - Down (Red) or Up (Black) - Down (Black), Post Height: 36 Inches, Belt Length: Standard Size of 2 meters, Base Weight: 8 kgs.	50	Set	250,000.00
7	Fogging Solution: Bac-To-Zero	Specifications: Revolutionary mist system, Complete interior coverage, Kills bacteria fast, Size Available: 1000mL	100	Unit	300,000.00
Other Information					
The bidders must download the attached documents in the associated component section.					

Created by Juliet Elaine Acuna
Date Created 29/09/2022

The PhilGEPS team is not responsible for any typographical errors or misinformation presented in the system. PhilGEPS only displays information provided for by its clients, and any queries regarding the postings should be directed to the contact person/s of the concerned party.